## KERN KB650-2N

Compact precision balance with large weighing range





Measuring system				
17164341114 3731611	Mager	Irina	eve	tom
	IVICAS	uniu	373	UCIII

External calibration
30 mg
20 g
10 mg
600 g (F1)
10 mg
65000
3 s
2 h
650 g
Strain gauge
* ct dwt g gn kg lb oz t tl (Cn) tl (HK) tl (Singap. Malays) tl (Tw) to

Display		
Display digit height:	9 mm	
Counting		
Counting resolution:	65000	
Mininum piece weight at piece counting (Laboratory:	10 mg	
Mininum piece weight at piece counting (Normal):	100 mg	

FunctionsConversion function:yesCounting function:yesPercentage determination:yesPRE-TARE function:yesSuspended weighing:HookEnvironmental conditionsMaximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:10 °CPower supplyCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter included:CH EURO UK USOperating time (Backlight off):30 h
Counting function:yesPercentage determination:yesPRE-TARE function:yesSuspended weighing:HookEnvironmental conditionsMaximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:10 °CPower supplyCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter included:CH EURO UK USOperating time (Backlight off):30 h
Percentage determination:yesPRE-TARE function:yesSuspended weighing:HookEnvironmental conditionsMaximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:10 °CPower supplyCCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
PRE-TARE function:yesSuspended weighing:HookEnvironmental conditionsMaximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:10 °CPower supplyCCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Suspended weighing:HookEnvironmental conditionsMaximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:10 °CPower supplyCCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Environmental conditions   Maximum humidity: 80 %   Maximum operating temperature: 40 °C   Minimum ambient temperature: 10 °C   Power supply C   Charging time: 10 h   Input voltage: 100 V - 240 V   Mains adapter: Mains adapter external   Mains adapter/adapter included: CH EURO UK US   Operating time (Backlight off): 30 h
Maximum humidity:80 %Maximum operating temperature:40 °CMinimum ambient temperature:10 °CPower supplyCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Maximum operating temperature:40 °CMinimum ambient temperature:10 °CPower supplyCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Minimum ambient temperature:10 °CPower supply10 hCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Power supplyCharging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Charging time:10 hInput voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Input voltage:100 V - 240 VMains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Mains adapter:Mains adapter externalMains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Mains adapter/adapter included:CH EURO UK USOperating time (Backlight off):30 h
Operating time (Backlight off): 30 h
Operating time (Backlight on): 15 h
Rechargeable battery: Rchrg. battery optional
Service
DAkkS Certificate: 963-127
Category
Brand: KERN
Category: Balances
Product Group: Precision balance
Packaging & shipping
Delivery: 24 h
Dimensions packaging (WxDxH): 360 x 230 x 180 mm
Gross weight: 2,200 kg
Net weight: 1,700 kg
Shipping method: Parcel service
Construction
Casing material: Plastic
Dimensions housing (WxDxH): 167 x 250 x 85 mm
Material weighing plate: stainless steel
Overall dimensions mounted 167 x 250 x 85 mm (WxDxH):
Revolving screw feet: yes

## KERN KB650-2N

Compact precision balance with large weighing range



## Piktogramme

STANDARD

		GLP PRINTER		% Percent	MOVE	UNDER
MULTI	DMS	1 DAY				

OPTION

