

CON200

Conductivity/TDS/ Salinity Meter

2014
New
Model

New design
Comfortable holding
Easy carrying
Simple Operation

65*40mm Large LCD
with backlight

IP67 rated Floats on water
One key to check through
all the settings



- New design, Comfortable holding, Easy carrying, Simple Operation
- 65*40mm, large LCD with backlight for easy meter information reading
- IP67 rated, dustproof and waterproof, Floats on water
- Measuring range: 0.000 uS/cm-400.0 mS/cm, Automatic range switching
- Unit display: uS/cm;mS/cm,TDS(mg/L), Sal(mg/L), °C
- One key to check through all the settings, including: cell constant, slope and all the settings
- Auto lock function
- 50 data sets memory stores and recalls
- Auto Power off saves battery after 10-mins non-use
- 2*1.5V 7AAA battery, long battery life
- CP337 Operating Carrying Pouch,

CS3000 Conductivity Sensor



- Standard 2-electrode Conductivity cell
- Epoxy/Graphite body
- with Built-in ATC (NTC22KO)
- Range: 0 to 30.0 mS/cm
- Cell constant K=1.0
- Φ 12 x120mm
- 8-pin connector
- 1m cable length

Specification		
Conductivity	Range	0.000 uS/cm-400.0 mS/cm
	Resolution	0.001 uS/cm-0.1 mS/cm
	Accuracy	± 0.5% FS
TDS	Range	0.000 mg/L ~ 400.0 g/L
	Resolution	0.001 mg/L ~ 0.1 g/L
	Accuracy	± 0.5% FS
Temperature	Range	-10.0 °C ~ 110.0 °C
	Resolution	0.1 °C
	Accuracy	± 0.2 °C
Power	Power supply	2*7 AAA batteries
	Working time	>500hrs
Environment	Humidity	-5-60 °C, Relative humidity<90%



www.cleaninst.com
Water Analysis Solutions