



## C-MAG HS 10 digital

/// Data Sheet

Magnetic stirrer with heating and ceramic heating plate which offers excellent chemical resistance.

- Powerful motor for stirring quantities of up to 15 I (H2O)
- Simultaneous digital display of target and actual temperatures via LCD display
- Directly connection for a PT 1000 temperature sensor enable a precise temperature control (included in delivery)
- Control accuracy in medium +/- 0,5 K (in combination with PT 1000)
- Display of actual temperature value in medium with 0,1 K resolution when using PT 1000 temperature sensor
- 3 operating modes to choose (standard, safe, adjustment protection)
- Fixed safety circuit of 550 °C



- Hot Top indicator >> hot surface warning to prevent burns!
- Digital error code display
- Elevated control panel for protection against leaking liquids



## **Technical Data**

N 1 6 6 1 10		
Number of stirring positions		
Stirring quantity max. per stirring position (H2O) [I]	15	
Motor rating output [W]	1.5	
Speed control	scale 0 - 6	
Speed range [rpm]	100 - 1500	
Stirring bar length max. [mm]	80	
Heat output [W]	1500	
Heating temperature range [°C]	50 - 500	
Heat control	stepless	
Heating rate heating plate [K/min]	5	
Connection for ext. temperature sensor	PT1000	
Fixed safety circuit [°C]	550	
Set-up plate material	ceramic	
Set-up plate dimensions [mm]	260 x 260	
Dimensions (W x H x D) [mm]	300 x 105 x 415	
Weight [kg]	8.308	
Permissible ambient temperature [°C]	5 - 40	
Permissible relative humidity [%]	80	
Protection class according to DIN EN 60529	IP 21	
Voltage [V]	230 / 120 / 100	
Frequency [Hz]	50/60	
Power input [W]	1520	



## **Wolf Laboratories Limited**

www.wolflabs.co.uk

Tel: 01759 301142

Fax:01759 301143

sales@wolflabs.co.uk







Use the above details to contact us if this literature doesn't answer all your questions.

Pricing on any accessories shown can be found by keying the part number into the search box on our website.

The specifications listed in this brochure are subject to change by the manufacturer and therefore cannot be guaranteed to be correct. If there are aspects of the specification that must be guaranteed, please provide these to our sales team so that details can be confirmed.





