KERN EMB 6000-1



Entry level laboratory balance with tremendous weighing performance



Category	
Brand	KERN
Product categoriy	Laboratory balance
Product group	School balance
Product family	EMB

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	6000 g
Readability [d]	0,1 g
Resolution	60.000
Linearity	± 0,3 g
Reproducibility	0,1 g
Tare range	6000 g
Default unit	g
Units	g dwt ozt oz
Adjustment options	Adjusting with external weight
Recommended adjusting weight	5 kg (M1)
Possible calibration points	5 kg
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,5 g
Maximum creep (15 minutes)	1 g
Maximum creep (30 minutes)	2 g

Approval

CE mark

Display	
Display type	LCD
Display screen size	58×18 mm
Display backlight	no
Display digit height	15 mm
Languages of the user interface	Symbol language
Construction	
Dimension housing (W×D×H)	170×244×39 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	plastic
Dimensions weighing surface (Ø)	150 mm
Functions	
Number of keys for operation	2
Auto-off interval(s) in battery mode/rechargeable battery mode	3 min
Tare function	manual (multi)
Underfloor weighing	Hook (included in delivery)
IP protection - complete device	_
Power Supply	
	9 V, 300 mA
Input voltage device / power [Max]	9 V, 300 mA Power adapter
Input voltage device / power [Max] Plug-in power supply type	Power adapter
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for	Power adapter Battery EURO UK
Input voltage device / power [Max] Plug-in power supply type Supplied power supply	Power adapter Battery EURO UK US
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional	Power adapter Battery EURO UK US CH
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional	Power adapter Battery EURO UK US
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time	Power adapter Battery EURO UK US CH
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging	Power adapter Battery EURO UK US CH Rchrg. battery optional
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating	Power adapter Battery EURO UK US CH Rchrg. battery optional
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 9 V block
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 9 V block Alkali(-Manganese)
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery connection	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 9 V block Alkali(-Manganese) Pad + Spring
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery connection Battery voltage	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 9 V block Alkali(-Manganese) Pad + Spring 9 V
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery connection Battery voltage Battery operating time	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 9 V block Alkali(-Manganese) Pad + Spring 9 V
Input voltage device / power [Max] Plug-in power supply type Supplied power supply Plug-in power supply / adapter for countries - optional Rechargeable battery optional Rechargeable battery charging time Rechargeable battery operating time - backlight off Battery Battery / accumulator type Battery connection Battery voltage Battery operating time Environmental conditions	Power adapter Battery EURO UK US CH Rchrg. battery optional 10 h 50 h 9 V block Alkali(-Manganese) Pad + Spring 9 V 12 h

1

35 °C

-20 °C

Ambient temperature [Max]

Storage temperature [Min]

KERN EMB 6000-1



Entry level laboratory balance with tremendous weighing performance

Storage temperature [Max]	60 °C
---------------------------	-------

Packing & Shipping	
Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	200×265×66 mm
Net weight	0,52 kg
Shipping method	Parcel service
Net weight approx.	0,55 kg
Gross weight approx.	0,70 kg
Shipping weight	0,7 kg

Services (optional)

Article number for DAkkS calibration	963-128
Article number for certificate of conformity (verification)	969-517

Pictograms

STANDARD











OPTION



