

KERN ORM 1NA

Digital measurement of refraction index for universal application

KERN



Category

Brand	Optics
Product category	Refractometer
Product group	Digital refractometer
Product family	ORM-NA

Measuring System

Measurement temperature [Min] (°C)	0 °C
Measurement temperature [Max] (°C)	40 °C
Precision	0,0003 nD 0,2 % 0,2 % 2 ‰ 0,002 sg
Measuring method	Total reflection
Measuring range Brix [Min]	0 %
Scales	Refractive index Brix Salt (NaCl) Salz (NaCl) ‰ spec. gravity
Measuring ranges	1,3330 nD - 1,4200 nD 0,0 % - 50,0 % 0,0 % - 28,0 % 0 ‰ - 280 ‰ 1,000 sg - 1,220 sg
Readabilities [d]	0,0001 nD 0,1 % 0,1 % 1 ‰ 0,001 sg
Readout Brix	0,1 %
Automatic temperature compensation (ATC)	✓
Accuracy Brix	±0,2 %

Measuring range refractive index [Min]	1,3330 nD
Measuring range refractive index [Max]	1,4200 nD
Readout refractive index	0,0001 nD
Accuracy refractive index	±0,0003 nD
Scale for Refractive index	✓
Measuring range salinity (NaCl) % [Min]	0 %
Measuring range salinity (NaCl) % [Max]	28 %
Readout salinity (NaCl) %	0,1 %
Accuracy salinity (NaCl) %	±0,2 %
Measuring range salinity (NaCl) ‰ [Min]	0 ‰
Measuring range salinity (NaCl) ‰ [Max]	280 ‰
Readout salinity (NaCl) ‰	1 ‰
Accuracy salinity (NaCl) ‰	±2 ‰
Scale salinity (NaCl) %	✓
Scale salinity (NaCl) ‰	✓
Measuring range salinity (spec. weight) [Min]	1,000
Measuring range salinity (spec. weight) [Max]	1,220
Readout salinity (spec. weight)	0,001
Accuracy salinity (spec. weight)	±0,002
Scale salinity (spec. weight)	✓
Appropriate calibration liquid	0 % (distilled water)
Measuring range Brix [Max]	50 %
Brix scale	✓
Area of application	Salt

Construction

Dimension (W×D×H)	121×58×25 mm
Refractometer type	Handheld refractometer
Scale - Display type	Digital
Prism lid	✓
Material prism	ZLaF3 lanthanum flint glass nd=1.85544

Functions

Averaging measurement	✓
Averaging measurement amount	15
IP protection - complete device	IP65
Auto-off interval(s) in battery mode/rechargeable battery mode	60 sec

KERN ORM 1NA



Digital measurement of refraction index for universal application

Power Supply

Supplied power supply	Battery
Battery / accumulator type	Alkali(-Manganese)
Battery connection	Pad + Spring
Battery capacity	1.300 mAh
Battery voltage	1,5 V

Environmental conditions

Storage temperature [Min]	-5 °C
Storage temperature [Max]	40 °C

Approval

CE mark	✓
---------	---

Services (optional)

Article number for factory calibration	961-290
--	---------

Packing & Shipping

Dimensions transport container (W×D×H)	170×110×50 mm
Delivery time	1 d
Dimensions packaging (W×D×H)	170×110×50 mm
Shipping method	Parcel service
Net weight approx.	0,15 kg
Gross weight approx.	0,35 kg
Shipping weight	0,31 kg

Product information

GTIN/EAN number	4045761335523
REACH classification	no prohibited substances

Pictograms

STANDARD

